

# PROFESSIONAL CONDENSATION DEHUMIDIFIERS, ROTOMOULDED DHP 65



PATENT

## DHP 65



- Easy to open for cleaning
- Can be cleaned with water jet
- Stackable
- Possibility of having on-board water pump and on-board water tank at the same time
- On-board humidistat
- Heavy-duty, rotomoulded casing
- High efficiency
- Hour counter
- Large water tank with automatic shut-off when full
- Possibility of continuous operation (24 h/day)



Stackable



Easy to open for cleaning



Digital control panel



**Water pump**  
Forcing height 4m  
**4512.441**

### Optional accessories

Specifications	Units	DHP 65
Capacity (30°C/80% RH)	l/24h	56
Capacity (20°C/60% RH)	l/24h	22
For rooms of approx.	m <sup>3</sup>	840
For restoration after flooding	m <sup>3</sup>	336
Refrigerant		R1234YF
Air flow	m <sup>3</sup> /h	500
Operating temperature range	°C	3-32/3-45
Operating humidity range	%	40-98/40-70
Power consumption	W	860
Power supply	V/Hz	220-240/1ph/50
Sound level	dB(A)	53
Compressor		Rotary
Tank capacity	l	10.5
Product size (l x w x h)	mm	570 x 530 x 700
Box size (l x w x h)	mm	730 x 580 x 840
Net/gross weight	kg	45/50
Pallet	pcs	4
Dual voltage		Available